



## Duct-wrap

ODE Duct-wrap is a glass mineral wool roll designed to be installed on ventilation ducts to prevent heat loss/gain and control condensation.

Aluminium foil acts as a vapour control layer and has a low emissivity.



Key Performances and Benefits	
Reaction to Fire classification	A1 non-combustible to EN 13501-1
Thermal conductivity (W/mk)	0.032 @10° C
Maximum service temperature	250°
Building standards	Complies with BS5422:2023
Density	24Kg/m <sup>3</sup>
BREEAM	A+ rating according to BRE Green Guide
Recycled content	Manufactured from >80% recycled glass
Corrosion	No acceleration of corrosion on aluminium, steel or copper plant equipment
Easy installation	Lightweight, no tear and low wastage
Long Life	Does not degrade, decompose, or become mouldy over time

## Specifications

Thickness mm	Thermal Conductivity @10°C (W/mk)	Length M	Width mm	Packs Per Pallet
25	0.032	16 (18*)	1200	24
40	0.032	10 (12*)	1200	24
50	0.032	8.5 (10*)	1200	18

\*Figures in brackets refer to vacuum packed rolls.

## Hyperpack Palletized Packaging

Thanks to the hyperpack packaging system, ODE Starflex glass wool facilitates:

- Loading more product per volume
- Loading and unloading using transpallet
- Minimum stocking cost
- Can be stored outdoors



More information and certification documents at [www.ode.com.tr/en](http://www.ode.com.tr/en)

ISO 27001 | ISO 9001 | ISO 14001 | ISO 50001 | ISO 45001

